

# GHK-EZ

Warm Air Heater

Stainless Steel

Heating medium LPG or natural gas  
Heat output 6 – 42 kW  
Air output 420 – 1,400 cbm/h  
fully automatic (EZ)



## Application:

- Exhibition halls
- Construction site heating
- Site drying
- De-icing
- Event rooms
- Marquees
- Airplane hangars
- Horticulture
- Grain drying
- Greenhouses
- Rooms for commercial use
- Industrial halls
- Storage rooms
- Agriculture
- Centres of logistics
- Production facilities
- Protection spaces
- Sports halls
- Stable heating
- Tennis halls
- Air domes
- Event tents
- Consumer markets
- Workshops

## Successful heating system for pig feed.

- Fully automatic (EZ) with electric ignition, ionisation flame control and supporting blower

Casing and combustion chamber each made of stainless steel. Completely with wall bracket for assembly outside the stable in main corridor. Several compartments can be heated by one unit due to motor flaps and flap controls. The hot air supply is done through matching ventilation tubes. Perfect for door hole ventilation and drizzling ceilings. The GHK types are operating modulating in connection with the heating output of 0 – 10 V of a climate computer.



GHK-EZ (fully automatic)

## GUSTAV NOLTING GmbH

Orbker Straße 38 | D-32758 Detmold

Phone +49 (0) 52 31.60 01-0

Fax +49 (0) 52 31.60 01-51

info@gustav-nolting-gmbh.de

www.gustav-nolting-gmbh.de



Technical Data				
Type	GHK-	15 EZ	25 EZ	40 EZ
Design			fully automatic (EZ)	
Type of gas/class			Natural gas and LPG / II 2 ELL 3 B/P	
<b>LPG model P/B:</b>				
Nominal heat loading capacity	kW	6 - 15	10 - 25	22 - 42
Connected pressure	mbar	50	50	50
Connected load	kg/h	0.4 - 1.2	0.8 - 1.95	1.7 - 3.3
<b>Natural gas model E/LL:</b>				
Nominal heat loading capacity	kW	7.5 - 15	15 - 25	22 - 42
Connected load	mbar	20	20	20
<b>General information:</b>				
Air output	cbm/h	420	800	1,400
Electric connection	V/Hz	230 / 50	230 / 50	230 / 50
Length	mm	1,070	1,200	1,400
Width	mm	300	350	350
Height	mm	520	520	550
Weight	kg	32	36	42
Air connection	mm	DN 150	DN 150	DN 150
Product ID no.			CE-0085 AQ 0230	