# Warm Air Heater

Stainless Steel

Heating medium electric current

Heat output 6 - 15 kW

Air output 900 - 1.400 cbm/h

Fully automatic

# Application:

- □ Exhibition halls
- Construction site heating
- Site drying
- □ De-icing
- Event rooms
- Marquees
- □ Airplane hangars
- Horticulture
- □ Grain drying
- Greenhouses
- □ Rooms for commercial use
- □ Industrial halls
- Storage rooms
- Agriculture
- □ Centres of logistics
- Production facilities
- □ Protection spaces
- ☐ Sports halls
- Stable heating
- □ Tennis halls
- ☐ Air domes
- □ Event tents
- □ Consumer markets
- Workshops

# Fast effective heat source.

Multiplex possibilities to use even in rooms not ventilated. Low weight and compact design - easy to transport and quick to store.

Can be optionally delivered with room thermostat for constant temperature and low power consumption.



- Fully automatic and low-noise performance
- □ Two heating stages selectable
- Ready for connection via supply line with CEE or two-pin grounded plug



### **GUSTAV NOLTING GmbH**

Orbker Straße 38 | D-32758 Detmold Phone +49 (0) 52 31 . 60 01-0 Fax +49 (0) 52 31 . 60 01-51 info@gustav-nolting-gmbh.de www.gustav-nolting-gmbh.de



Туре	NE-	6/9	9 / 15	
Nominal heat loading capacity	kW	6.0 - 9.0	9.0 - 15.0	
Air output	cbm/h	900	1,400	
Electric connection	V/Hz	3~400/50		
Current consumption	Α	13	23	
Length	mm	500	580	
Width	mm	320	320	
Height	mm	470	470	
Weight	kg	17	20	
Possibility to control			Possibility to connect room themostat with cable (optional accessories)	