

NG

Warm Air Heater

Stainless steel

Heating medium LPG / I 3 P
Heat output 18 - 100 kW
Air output 1.100 - 2.800 m³/h
Fully automatic



Application:

- ☐ Exhibition halls
- ☒ Construction site heating
- ☒ Site drying
- ☒ De-icing
- ☐ Event rooms
- ☐ Marquees
- ☐ Airplane hangars
- ☒ Horticulture
- ☒ Grain drying
- ☒ Greenhouses
- ☐ Rooms for commercial use
- ☐ Industrial halls
- ☐ Storage rooms
- ☒ Agriculture
- ☐ Centres of logistics
- ☐ Production facilities
- ☐ Protection spaces
- ☐ Sports halls
- ☐ Stable heating
- ☐ Tennis halls
- ☐ Air domes
- ☐ Event tents
- ☐ Consumer markets
- ☐ Workshops

Handy and powerful:

The units of our NG series are technically finished, fair in consumption and variable in use inside rooms with ventilation.

Type NG 35 - 100

Fully automatic with electric ignition and ionisation flame control. Uncomplicated connection possibility to use a room thermostat via plug connection.



Included to delivery is a gas hose with pressure control (gas bottles 5.0 - 33.0 kilos).
Heating capacity can be chosen variably within the stated range.

All units are optimally intended for frost-free maintenance of building sites and are often used for grain drying in agriculture.



GUSTAV NOLTING GmbH

Orbker Straße 38 | D-32758 Detmold
Phone +49 (0) 52 31 . 60 01-0
Fax +49 (0) 52 31 . 60 01-51
info@gustav-nolting-gmbh.de
www.gustav-nolting-gmbh.de



Technical Data						
Type	NG-		35	50	75	100
Model			Fully automatic			
Nominal heat loading capacity	kW		18.0 - 35.0	25.0 - 50.0	35.0 - 70.0	50.0 - 100.0
Air output	cbm / h		1,100	1,400	2,000	2,800
Connected pressure	bar		2.5 - 10.0			
Connection value	kg / h		1.41 - 2.73	1.95 - 3.91	2.73 - 5.47	3.91 - 7.81
Electric connection	V / Hz		230 / 50			
Current consumption	A		0.48	0.48	0.60	0.92
Length	mm		500	650	800	1,000
Width	mm		320	320	370	370
Height	mm		460	460	520	520
Weight	kilos		14	16	21	26
Product ID number			CE-0085 AQ 0232			
Control			Fully automatic with electrical ignition and possibilities to connect a room thermostat			

Subject to changes of dimensions and technical data (Version: 2024-03)