



The blowers can be supplied in any RAL colour

Standard RAL colour 7035

Reliable in use - worldwide

Nolting pressure control systems in compact construction with fish plates for wall mounting.

Our units DG-500 are technically fully developed and daily proof thousands of times worldwide as safe blowers for air cushion roofs.

Additional control DG-500 (possible)

- Min. pressure alarm
- Max. pressure alarm
- optical and audible signal
- battery with maintenance charging
- on / off switch for alarm system



GUSTAV NOLTING GmbH

Orbker Straße 38 | D-32758 Detmold

Phone +49 (0) 52 31 . 60 01-0

Fax +49 (0) 52 31 . 60 01-51

info@gustav-nolting-gmbh.de

www.gustav-nolting-gmbh.de



Technical Data					
Type	DG-	500-1	500-2	500-3	500-4
Air output blower	cbm/h	500	500	500	490
External pressure (adjustable up to)	Pa	560	450	450	540
Supply air connecting piece	mm	40	40	40	40
Sound	dB/A	53	50	53	53
Motor capacity	W	370	120	120	150
Air filter		F 5	F 5	F 5	F 5
Electric connection	V/Hz	230 / 50	230 / 50	230 / 50	110 / 60
Length	mm	600	600	400	600
Width	mm	500	500	450	500
Height without connecting piece	mm	450	450	400	450
Weight about	kg	40	35	30	40

Subject to changes of dimensions and technical data (Version: 2019-08)