



The blowers can be supplied in any RAL colour wanted.

Standard RAL colour 7035

## Reliable in use - worldwide

Nolting pressure control systems in compact construction with fish plates for wall mounting.

Our units DG-500 are technically fully developed and daily proof thousands of times worldwide as safe blowers as safe blowers for air cushion roofs.

### Additional control DG-500 (possible)

- Min. pressure alarm
- Max. pressure alarm
- optical and audible signal
- battery with maintenance charging
- on / off switch for alarm system



### **GUSTAV NOLTING GmbH**

Orbker Straße 38 | D-32758 Detmold

Phone +49 (0) 52 31 . 60 01-0

Fax +49 (0) 52 31 . 60 01-51

info@gustav-nolting-gmbh.de

www.gustav-nolting-gmbh.de



Technical Data		DG-	500-1	500-2	500-3	500-4
Type						
Air output blower	cbm / h		500	500	500	490
External pressure (adjustable up to)	Pa		<b>560</b>	<b>450</b>	450	540
Supply air connecting piece	mm		50	50	50	50
Sound	dB/A		53	50	53	53
Motor capacity	W		370	120	120	150
Air filter			F 5	F 5	F 5	F 5
Electric connection	V/Hz		230 / 50	230 / 50	230 / 50	<b>110 / 60</b>
Length	mm		600	600	<b>400</b>	600
Width	mm		500	500	<b>450</b>	500
Height without connecting piece	mm		450	450	<b>400</b>	450
Weight about	kilos		40	35	30	40

Subject to changes of dimensions and technical data (Version: 2021-01)