

HSW-T

Warm Air Heater

Stainless Steel

Heating medium fuel oil EL, diesel

Heat output 49 - 97 kW

Air output 2,050 - 3,300 cbm/h

Fully automatic



Application:


- Exhibition halls
- Construction site heating
- Site drying
- De-icing
- Event rooms
- Marquees
- Airplane hangars
- Horticulture
- Grain drying
- Greenhouses
- Rooms for commercial use
- Industrial halls
- Storage rooms
- Agriculture
- Centres of logistics
- Production facilities
- Protection spaces
- Sports halls
- Stable heating
- Tennis halls
- Air domes
- Event tents
- Consumer markets
- Workshops

Mobile design with integrated tank.

Operation without exhaust system (open combustion chamber).

Most suitable for heating of good ventilated spaces
(no living or sitting rooms)

- Fully automatic with flame control
- Combustion chamber completely made of high heat-resistant stainless steel (long lasting use)
- Current connection with two-pin grounded plug (mains supply line of 5m)
- Connection of external room thermostat possible



GUSTAV NOLTING GmbH

Orbker Straße 38 | D-32758 Detmold

Phone +49 (0) 52 31 . 60 01-0

Fax +49 (0) 52 31 . 60 01-51

info@gustav-nolting-gmbh.de

www.gustav-nolting-gmbh.de



Technical Data

Type	HSW-	50 T	100 T
Nominal heat loading capacity	kW	49.0	97.0
Air output	cbm / h	2,050	3,300
Electric connection	V / Hz	230/50	
Current consumption	A	1.75	4.8
Length	mm	1,300	1,500
Width	mm	520	650
Height	mm	750	890
Weight	kilos	59	85
Tank volume	l	75	150
Consumption	kg / h	4.2	8.2

Subject to changes of dimensions and technical data (Version: 2013-06)