

# KL-200 L

## Warm Air Heater

Stainless Steel

Heating medium natural gas and LPG

Heat output 115 - 185 kW

Air output 7,000 - 11,200 cbm/h



### Einsatzbereiche:

- Exhibition halls
- Construction site heating
- Site drying
- De-icing
- Event rooms
- Marquees
- Airplane hangars
- Horticulture
- Grain drying
- Greenhouses
- Rooms for commercial use
- Industrial halls
- Storage rooms
- Agriculture
- Centres of logistics
- Production facilities
- Protection spaces
- Sports halls
- Stable heating
- Tennis halls
- Air domes
- Event tents
- Consumer markets
- Workshops

### Cost-effective and easy to maintain.

For heating poultry houses, effective and clean:

### Proven technology as standard:

- Warm air heater the output of which is adapted to practical requirements
- Housing / combustion chamber made of stainless steel
- No exhaust gas emissions in stable => low CO<sup>2</sup> content
- Electrical connection with connector plug
- Splash-proof control box
- Proven, high-quality built-in components
- Separate burner, alternatively for natural gas or LPG
- Control possible via room thermostat or ventilation control



### GUSTAV NOLTING GmbH

Orbker Straße 38 | D-32758 Detmold

Phone +49 (0) 52 31 . 60 01-0

Fax +49 (0) 52 31 . 60 01-51

info@gustav-nolting-gmbh.de

www.gustav-nolting-gmbh.de



### Technical Data

Type		KL-200 L
Frequency converter		Ja
Nominal heat loading capacity	kW	127 - 200
Rated heat output	kW	115 - 185
Air output	cbm/h	7,000 - 11,200
External pressure	Pa	300
Electrical connection		3 x 400 V, N, PE / 50 Hz
Motor output	kW	2.6
Connected load, electrical	kW	4.0
Protection, to be made by customer max.	A	32
Rated current	A	8.2
Connector plug		CEE 32 A
Dimensions L / W / H	mm	2,400 / 800 / 1,300
Adapter for exhaust air	mm	200
Blow-out connection	standard mm	550
Blow-out adapter	optionally mm	2 x 400 oder 4 x 300
Weight	kilos	490
Sound pressure level (distance 1m)	about dB (A)	69
Increase in temperature	k	43

Subject to changes of dimensions and technical data (Version: 2020-05)