KL-600

Warm Air Heater

Heating Medium oil EL or gas Heat output 600 kW Air output 50,000 cbm/h free blowing

Stainless Steel



Application:

- Exhibition halls
- Construction site heating
- ☐ Site drying
- De-icing
- Event rooms
- Marquees
- Airplane hangars
- □ Horticulture
- ☐ Grain drying
- ☐ Greenhouses
- ☐ Rooms for commercial use
- Industrial halls
- Storage rooms
- □ Agriculture
- Centres of logistics
- Production facilities
- ☐ Protection spaces
- ☐ Sports halls
- □ Stable heating
- ☐ Tennis halls
- ☐ Air domes
- Event tents
- Consumer markets
- □ Workshops

Unloading, Setting up, Ready for heating!

Compact and strong type of unit - perfectly suitable for different applications when heating and tempering event rooms, marquees, industrial halls, storage rooms and construction sites. The construction and design fulfill the special requirements of rental companies for high functionality, economical and long-lasting use.



- Unit for outside installation
- Basic frame with fork lift guides for mobile use
- all components in a compact housing
- maintenance-friendly arrangement of the components
- individual design on request



Blow-out adapter

Burner hood

GUSTAV NOLTING GmbH

Orbker Straße 38 | D-32758 Detmold Phone +49 (0) 52 31 . 60 01-0 Fax +49 (0) 52 31 . 60 01-51 info@gustav-nolting-gmbh.de www.gustav-nolting-gmbh.de



Technical Data			
Туре			KL-600
Frequency converter			Yes
Nominal heat loading capacity		kW	660
Rated heat output		kW	600
Air output		cbm / h	41,000
External pressure		Pa	500
Electrical connection			3 x 400 V, N, PE 50 Hz
Motor output		kW	15.0
Connected load, electrical		kW	16.0
Protection, to be made by customer		Α	32.0
Rated current		А	32.0
Connector plug			CEE 32 A
Dimensions L / W / H		mm	4,450 / 1,580 / 2,300
Adapter for exhaust air		mm	350
Blow-out connection	standard	mm	3 x 500
Blow-out adapters	ptionally	mm	2 x 710 / 4 x 500
Weight		kilos	2,250
Sound pressure level (distance 1m)		dB (A)	73
Increase in temperature		k	to 42