# NG-L/LE

## Warm Air Heater

Stainless Steel

Application:

□ Site drying

Event roomsMarqueesAirplane hangarsHorticulture

□ Grain drying

☐ Greenhouses

□ Industrial halls

☐ Storage rooms

□ Centres of logistics

□ Production facilities

□ Protection spaces
□ Sports halls
■ Stable heating
□ Tennis halls
□ Air domes
□ Event tents

Consumer marketsWorkshops

Agriculture

□ De-icing

□ Exhibition halls

□ Construction site heating

☐ Rooms for commercial use

Heating medium natural gas and LPG Heat output 10 - 100 kW Air output 500 - 7,500 cbm/h

Fully automatic





### Effective, economical and of low maintenance.

Proven as well as effective as stable heating: Fully automatic with infrared flame monitoring, electrical ignition, supporting air fan and open combustion chamber (operation without exhaust system).

#### Proved technology by standards:

- Five warm air heaters matching in terms of performance with the requirements of practice - easily transportable to each gas type (except NG-LE-10)
- Casing/combustion chamber made of stainless steel
- ☐ Gas connection 3/4" or 1/2" inside thread
- Low-maintenance burner
- Electric connection with two-pin grounded plug
- ☐ Drip-proof switch box
- Automatic ignition
- Control possible by room thermostat or ventilation control
- Three-point suspension (tags are fixed)

## **GUSTAV NOLTING GmbH**

Orbker Straße 38 | D-32758 Detmold Phone +49 (0) 52 31 . 60 01-0 Fax +49 (0) 52 31 . 60 01-51 info@gustav-nolting-gmbh.de www.gustav-nolting-gmbh.de





NG-LE-10



NG-L

Technical Data						
Туре		NG-LE-10	NG-L-30	NG-L-50	NG-L-80	NG-L-100
Type of gas / class		Natural gas / I 2 E	Natural gas and LPG / II 2 ELL 3 B/P			
Nominal heat loading capacity	kW	10	30	50	80	100
Air output	cbm / h	500	1,600	2,300	4,100	7,500
Connected pressure	bar	0.02	0.02 or 0.05			
Connection value	kg / h	-	2.33	3.89	6.23	7.78
Electric connection	V / Hz		230 / 50			
Current consumption	Α	0.3	0.85	1.0	2.9	3.7
Length of throw	m	15	30	40	50	60
Length	mm	500	990	990	1,150	1,250
Width	mm	450	445	510	560	640
Height	mm	450	312	365	410	510
Weight	kilos	16	35	41	45	56
Product ID number		CE-0085 BN 0001				