## **NE**Warm Air Heater

Stainless Steel

Heating medium electric current

Heat output 6 - 15 kW

Air output 900 - 1.400 cbm/h

Fully automatic





## Application:

- □ Exhibition halls
- Construction site heating
- Site drying
- □ De-icing
- Event rooms
- Marquees
- □ Airplane hangars
- Horticulture
- □ Grain drying
- Greenhouses
- □ Rooms for commercial use
- □ Industrial halls
- Storage rooms
- Agriculture
- □ Centres of logistics
- Production facilities
- ☐ Protection spaces
- □ Sports halls
- Stable heating
- □ Tennis halls
- ☐ Air domes
- □ Event tents
- □ Consumer markets
- Workshops

## Fast effective heat source.

Multiplex possibilities to use even in rooms <u>not</u> ventilated. Low weight and compact design - easy to transport and quick to store. Can be optionally delivered with room thermostat for constant temperature and low power consumption.

- Fully automatic and low-noise performance
- ☐ Two heating stages selectable
- ☐ Ready for connection via supply line with CEE or two-pin grounded plug



## **GUSTAV NOLTING GmbH**

Orbker Straße 38 | D-32758 Detmold Phone +49 (0) 52 31 . 60 01-0 Fax +49 (0) 52 31 . 60 01-51 info@gustav-nolting-gmbh.de www.gustav-nolting-gmbh.de



_				
Туре	NE-	6 / 9	9 / 15	
Nominal heat loading capacity	kW	6.0 - 9.0	9.0 - 15.0	
Air output	cbm/h	900	1,400	
Electric connection	V/Hz	3.	3~400/50	
Current consumption	Α	13	23	
Length	mm	500	580	
Width	mm	320	320	
Height	mm	470	470	
Weight	kg	17	20	
Possibility to control			Possibility to connect room themostat with cable (optional accessories)	